

MPW 22 2/2 way, MPW 23 3/2 way stainless steel valve



A. SOLENOID VALVES

- Series MPW 22 – 2/2 directly driven stainless steel,
- series MPW 23 – 3/2 directly driven stainless steel,
- body material: stainless steel 304,
- valve can operate in any position,
- high reliability, long life,
- medium: air, water,
- maximum pressure: 60 Bar (6 MPa),
- ambient temperature: $-40 \div +60 \text{ }^{\circ}\text{C}$,
- fluid temperature: $-40 \div +180 \text{ }^{\circ}\text{C}$,
- sealing: FPM,
- medium viscosity $< 20 \text{ cSt}$,
- response time: open 5–20 ms,
- connector specification/el. connection: DIN4400/EN175301-803, IP65,
- standard voltage 230 V/50 Hz, possibility of 12VDC, 24VDC, 24VAC,
- power consumption 19 VA,
- voltage tolerance: $\pm 10 \%$.

Model	MPW22					MPW23		
Orifice (mm)	2	3	3,5	4	5	2 (NC)	2 (NO)	2 (universal)
Working differential pressure (Bar)	0–55	0–26	0–16	0–14	0–10	0–7	0–20	0–8
Kv factor (l/min)	1,8	3,5	4,3	5,4	6,8	1,8	1,8	1,8

